



5" LCD Wired Reversing Kit

Colour LCD Monitor & Night Vision Camera Safeguard family, pedestrian & protect your vehicle!







- Colour weather resistant wide angle camera & LCD monitor plug into your cigarette lighter or reversing lights
- Keep an eye on your rear-view when you need to
- An easy way to assist with parking & reversing
- See other vehicles as they approach from behind
- Colour camera switches automatically to B&W infra-red night vision of up to 9ft (3m)
- Automatic mirror flip feature: mount camera upside down & screen changes to correct way up
- Mount monitor to the inside ceiling of your vehicle for best results



Protect rear bumpers from accidental damage



View any blind spot



Manoeuvre in tight spaces easily



Prevent risk of injury to pedestrians

Enquiries: info@swann.com.au Product Code: SW244-VR5







5" LCD Wired Reversing Kit

Colour LCD Monitor & Night Vision Camera

Safeguard family, pedestrian & protect your vehicle!

4 Step Installation

Step I: Mount LCD to dash

Step 2: Connect LCD power wire to reversing light fuse or


12V power source

Step 3: Run cable & mount camera to the back of the car

Step 4: Connect power to the reversing light







Technical Specifications Camera Specifications

1/4" CMOS image sensor Pickup Device: Number of Pixel: PAL: 720x576; NTSC: 720x478 System of signal: PAL/NTSC. Horizontal Resolution: 420 TV Line

0.5 Lux/F4.5 Minimum Illumination: Up to 9ft (3m) Night Vision Range: Backlight compensation: Auto

1/50(1/60)~1/100,000sec Flectronic Shutter:

White Balance: Auto >48dB S/N Ratio: Gamma Consumption: >0.45 Operating Temperature: -20 ° C~60 ° C Sync. System: Internal 1.0Vp-p/75Ω Video Output: DV12V. < 150mA Power Supply: View Angle: 90 degree

LCD Monitor Specifications

Size of screen: 5 inches TFT Screen Screen LCD Profile Ratio: Ratio 4:3

0.107mm (H) x 0.319mm (V) Bot:

960 (H) x 234 (V) Display Resolution: Contrast 150:1 Contrastness: 300cd/m Brightness: Reponse Time (ms): R:30/F:50 U:15/D:35 L/R:55 Viewing Angle: Diplay of imitate quantity: OSD Display

Adjustment item of imitate quantity:

Colour system: Video input: Audio input: Sound System: Power: Picture display mode: Source of light:

Life expectanty of lamp: Line frequency of system: Spot frequency of system: Function of backing car:

Language:

Outside dimension:

Net weight: Operation Temperature: Storage Temperature: Power consumption:

Brightness, contrastness, resolution, color, volume (0-100) PAL, N3.58,N4.43 IVP-P 750HM(TWO ROUTE)

1.5VP-P(ONF ROUTF) B/G(5.5M),I(6.0M),D/K(6.5M)

DC+12V+/-10% 4:3/16:9/16:9-1 CCFL About 10,000

15.625kHz (PAL) /15.670kHz (NTSC) 50Hz (PAL) / 60Hz (NTSC) Up/Down, Left/Right Manual English, Russian, German, French, Spanish,

Portugese, Italian & Dutch changable

menu language W163mm x H133mm x T38mm (inc headset)

around 430gr $0 \sim 40$ -20~-60 around 8w

Package Contents:

- Wired Camera
- 5" I CD screen
- LCD stand
- Cigarette lighter adaptor
- Instruction Guide
- ** This product will be set to the TV standard of the country of sale







